Quadratec® PreRunner Light Kit

Installation Manual: for Jeep Wrangler ('07-'18) JK Vehicles #97109.1140





PARTS LIST:

Prerunner Light Bracket Prerunner Light Wiring Harness M5 x 16mm SS Button Head Screw QTY 2 M5 SS Flat Washer QTY 2 M5 SS Split Lock Washer QTY 2 M5 Clip-On U-Nut QTY 2 Wire Ties QTY 6

REQUIRED TOOLS:

Safety Glasses 3mm Hex/Allen Wrench Key Phillips Head Screwdriver Small Flat Blade Screwdriver Diagonal Pliers (wire cutters)

ACAUTION A


READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING TO INSTALL THIS PRODUCT. ALWAYS WEAR SAFETY GLASSES DURING INSTALL.



Install Preparation for '07 - '18 JK Wrangler



Put on safety glasses. Open the hood of your Jeep[®]. Put the prop rod into the correct slot to hold hood open (FIG 1).



Locate the six plastic fasteners that secure the front grille to the upper body support (FIG 2).



Depending on your model year, pry up or unscrew the plastic fasteners (6 total) using a small screw driver. Early vehicles may feature phillips head screws, but most vehicles have a pry-up rivet as shown (FIG 2). First remove the center, then remove the body of each plastic retainer (FIG 3). Set rivets & screws aside in a safe place for re-installing the grille.



Next, Gently tilt the grille forward and then gently pop the lower portion of grille from its retaining clips. (FIG 4)



Disconnect the front turn signals by sliding the red locking tab backwards, depress the black latch and pull outward. (FIG 5)



PreRunner Lights Install for '07 - '18 JK Wrangler




Assemble the Bracket and wiring harness. Start by pulling back the wire loom and grommet at each lamp. (FIG 6)




Slide the wiring through the cutout in each mount. (FIG 7)



Push the grommet into the mount, push the lamp into the grommet until flush and replace wire loom. (FIG 8)



Lay the harness along the bracket and secure with the provided wire ties. Trim excess wire tie as necessary. (FIG 9)



Note: The factory wiring harness will be routed behind the bracket as shown. (FIG 10)



You will need to reach under and pull out the wiring harness to position it in front of the bracket as shown. (FIG 11)




The Trusted Source

PreRunner Lights Install for '07 - '18 JK Wrangler




With factory wiring harness out of the way, Install the Clip on U-nuts into place on the radiator support. (FIG 12)



Next, Mount the light bracket to u-nuts with the provided button head screws, lock washers and flat washers using a 3mm Hex Key. (FIG 13)



Route the wiring harness through radiator support, through drivers side fender flare along side original wiring and secure as needed using the provided wire ties. Trim excess wire tie as necessary. (FIG 14)



Disconnect the original wiring harness from side marker and plug in the Pre-Runner harness to the original vehicle connector and then back to the side marker. (FIG 15)

Reinstall the Grill and plug in turn signals in the reverse order of the disassembly.

ACAUTION A

ALWAYS CHECK TURN SIGNAL AND HEADLIGHTS FUNCTION BEFORE DRIVING AFTER PRERUNNER LIGHT INSTALLATION.









Quadratec® Exclusive Three Year Limited Warranty

Your Quadratec[®] branded accessories are covered by the following **Limited Warranty** provided exclusively by Quadratec, Inc., 1028 Saunders Lane, West Chester PA 19380.

This **Limited Warranty** is the only warranty made in connection with your purchase. Quadratec neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or **Limited Warranty**. This **Limited Warranty** does not apply and is not cumulative to any accessory or part distributed by Quadratec for which the Manufacturer provides a separate written warranty.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to Quadratec branded accessories first sold in the United States, Quadratec warrants to the initial retail purchaser only that your Quadratec accessory shall be free of defects in material and workmanship: for a period of three (3) years from date of retail purchase.

This **Limited Warranty** is not assignable and shall terminate upon sale of the vehicle upon which the Quadratec accessory is installed or other transfer third persons.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is limited to 3 year from date of initial retail sale. Quadratec reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this **Limited Warranty** as a condition of warranty service and, (b.) make future revisions to this product and **Limited Warranty** without prior notice or obligation to upgrade your product.

What is Not Covered:

Your Quadratec **Limited Warranty** does not cover products or parts Quadratec determines to have been damaged by or subjected to: (a.) installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon Quadratec inspection and at Quadratec's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact Quadratec to obtain a RGA number (610-701-3336). All labor, removal, shipping and installation costs are customer's responsibility.

Other Limitations - Exclusion of Damages -Your Rights Under State Law:

In consideration of the purchase price paid, neither Quadratec nor any independent Quadratec distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This **Limited Warranty** gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and /or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©Quadratec, Inc. 2019. All Rights Reserved. 2.26.19 A4 Version

Part #12999.3127

